



QUICK REFERENCE GUIDE

- ❖ All tile **must be** complete before field measurement can occur
- ❖ CCS prefers a threshold under **all** units (even GW doors) to assure a water-tight seal
- ❖ **76"** is generally an adequate maximum height for 3/8" Glasstec units, as additional height increases the likelihood of bowing and deflection.
- ❖ CCS prefers a header when possible to increase stability and reduce deflection
- ❖ **No** glass-to-glass hinges if possible. CCS prefers the pivot hinge or wall mount pivots. Safety and better clearances are achieved with the pivot hinge system, distributing the weight of the glass in a more downward, non-lateral direction.
- ❖ On GAPW units (units without a header) the hinge side **must be** plumb +/- 3/16"
- ❖ Neo-Angles generally have a 90° door with mitered panels
- ❖ Due to the possibility of bowing, CCS prefers 90° units over mitered ones
- ❖ Diamon-Fusion is highly recommended by CCS on **all** units. One cannot overestimate the convenience this product provides.
- ❖ Notched panels **must be** a minimum of 6" on bottom of notch and 3/4" on top
- ❖ CCS recommends adding back to back 6" C-pull handles to all Centec hinged and Lucette hinged doors for a cleaner and more modern look.
- ❖ Centec sliders are the best for tubs
- ❖ CCS recommends 3/8" glass for Centec shower units to reduce deflection

Construction Consultant Services, Inc.
4001 Camden Drive, Jefferson, MD 21755
www.showerdoorexerts.com